

# DÉCOR COBBLES ON-MESH

## APPLICATION INSTRUCTIONS FOR COBBLES ON-MESH

SOURCE	China	SIZE	55mm x 50mm Running Bond
THICKNESS	30mm	APPEARANCE	Natural Granite Cobbles On-Mesh. Interlocking Patterns
PRODUCTION	Small pieces of granite epoxy glued together to make a sheet.		
FINISHES	FLAMED- smooth	SPLIT- rough	TUMBLED- split surface slightly tumbled
COLOURS	1. Putian Red - Deep Red 4. Dark Grey - Grey	2. Pink Quartz - White with Pink Hues 5. Light Grey - Speckled White	3. Putian Black - Deep Black 6. Yellow Granite - Speckled Wheat

1. Ensure that all surfaces are clean and free of all loose material and dust.
2. Do not apply mats to a previously painted, sealed or coated surface. Specialist advice is to be sought for treatment of painted, sealed or coated surfaces prior to fixing matting.
3. Adhesive: When placing the adhesive spread approximately 12mm thick to the same size as mat. It is very important to ensure that the adhesive penetrates the nylon mesh and covers the entire back of the stone pieces. Press the stone mats into position and use a soft mallet to ensure spread of adhesive.
4. Ensure that the adhesive being used is suitable for use with stone products and for the particular application, i.e. interior, exterior, water features etc.
5. When using the matting for a water feature it is very important to ensure that the adhesive used is suitable for immersion in water and that a compatible waterproof coating had been applied prior to installation.
6. Prior to grouting it is recommended that the natural stone is treated with a grout-release/sealant to prevent grout adhering onto the stone pieces.
7. Grouting: use a dry grout mix (3:1) and brush into mortar joints. Then use a light mist to set the grout. This will help when cleaning the cobbles due to corrugations in the stone.
8. It is recommended that the natural stone is sealed with a suitable sealant to protect the stone surface and to highlight the natural stone colour.
9. Where Décor Cobbles-on-Mesh are to be laid in a non-vehicle traffic area a 100mm compacted road base can be used.
10. Sealant should be re-applied as per recommendations of the manufacture's guidelines.

**IT IS RECOMMENDED THAT FOR THE BEST RESULTS, A PROFESSIONAL TRADESPERSON CARRY OUT ALL INSTALLATION WORK.**

### CONTACT DETAILS:

Décor Stone

84-90 Highbury Road Burwood VIC 3125

PH: (03) 9888 9888

W: [www.decorstone.com.au](http://www.decorstone.com.au)

F: (03) 9888 9884

E: [sales@decorstone.com.au](mailto:sales@decorstone.com.au)

*Décorative Stone Solutions*