

DÉCOR CRAZY PAVING

CRAZY PAVING INSTALLATION MATERIALS

KERABOND PLUS ADHESIVE (a powder to which Isolastic needs to be added)

- o 24hr drying period at 23°C for light foot traffic
- o 14 days to cure
- o Clean tools with water and surface with a damp cloth

ISOLASTIC 50 (50% strength synthetic latex liquid)

- o Mix with Kerabond Plus adhesive
- o Helps deal with hot and cold temperature changes - movement and contraction; thermal exposure
- o Increases bond strength
- o New concrete should be cured for 6 months

MAPELASTIC SMART

- o Cementitious Waterproofer & Efflorescence barrier
- o Use to prime surfaces
- o Apply to a clean surface
- o Absorbent surfaces should be dampened first
- o Protect from water for 24 hours
- o Don't fill ponds for 5days.
- o Remains flexible
- o Clean tools with water before adhesive sets.

DURA SLATE GLOSS SEALER

- o Solvent based sealer
- o Enhances the colour and gives a wet look
- o Apply 1 coat before grout to make cleaning easier
- o Apply a minimum of 2 coats

CONTACT DETAILS:

Décor Stone

84-90 Highbury Road Burwood VIC 3125

PH: (03) 9888 9888

F: (03) 9888 9884

W: www.decorstone.com.au

E: sales@decorstone.com.au