

Products used for laying Crazy Paving

Kerabond Plus adhesive (a powder to which Isolastic needs to be added)

- o 24hr drying period at 23oC for light foot traffic
- o 14 days to cure
- o Clean tools with water and surface with a damp cloth

Isolastic 50 (50% strength synthetic latex liquid)

- o Mix with Kerabond Plus adhesive
- o Helps deal with hot and cold temperature changes - movement and contraction; thermal exposure
- o Increases bond strength
- o New concrete should be cured for 6 months

Mapelastic Smart

- o Cementitious Waterproofing & Efflorescence barrier
- o Use to prime surfaces
- o Apply to a clean surface
- o Absorbent surfaces should be dampened first
- o Protect from water for 24 hours
- o Don't fill ponds for 5days.
- o Remains flexible
- o Clean tools with water before adhesive sets.

Dura Slate Gloss Sealer

- o Solvent based sealer
- o Enhances the colour and gives a wet look
- o Apply 1 coat before grout to make cleaning easier
- o Apply a minimum of 2 coats

Dura Slate Finish/Primer

- o Water based sealer
- o Product retains a lighter natural look
- o Apply 1 coat before grout to make cleaning easier
- o Apply a minimum of 2 coats
- o The second coat can be Dura Slate Gloss Sealer can be applied for increased protection from wear
- o Clean tools with water.

::: showroom :::

84-90 Highbury Road Burwood

Victoria

telephone: (03) 9888 9888

facsimile: (03) 9888 9884

email: sales@decorstone.com.au