

Application Instructions for DécoR Cobbles On-Mesh

Source:	China												
Colours:	<table><tr><td>1. Putian Red</td><td>- Deep Red</td><td>2. Pink Quartz</td><td>- White with Pink Hues</td></tr><tr><td>3. Putian Black</td><td>- Deep Black</td><td>4. Dark Grey</td><td>- Grey</td></tr><tr><td>5. Light Grey</td><td>- Speckled White</td><td>6. Yellow Granite</td><td>- Speckled Wheat</td></tr></table>	1. Putian Red	- Deep Red	2. Pink Quartz	- White with Pink Hues	3. Putian Black	- Deep Black	4. Dark Grey	- Grey	5. Light Grey	- Speckled White	6. Yellow Granite	- Speckled Wheat
1. Putian Red	- Deep Red	2. Pink Quartz	- White with Pink Hues										
3. Putian Black	- Deep Black	4. Dark Grey	- Grey										
5. Light Grey	- Speckled White	6. Yellow Granite	- Speckled Wheat										
Size:	55cm x 50cm												
Thickness:	3cm												
Appearance:	Natural Granite Cobbles On-Mesh. Interlocking Patterns												
Production:	Small pieces of granite epoxy glued together to make a sheet.												

Technical Instructions for installing DécoR Cobbles On-Mesh.

1. Ensure that all surfaces are clean and free of all loose material and dust.
2. Do not apply mats to a previously painted, sealed or coated surface. Specialist advice is to be sought for treatment of painted, sealed or coated surfaces prior to fixing matting.
3. Adhesive: When placing the adhesive spread approximately 12mm thick to the same size as mat. It is very important to ensure that the adhesive penetrates the nylon mesh and covers the entire back of the stone pieces. Press the stone mats into position and use a soft mallet to ensure spread of adhesive.
4. Ensure that the adhesive being used is suitable for use with stone products and for the particular application, i.e. interior, exterior, water features etc.
5. When using the matting for a water feature it is very important to ensure that the adhesive used is suitable for immersion in water and that a compatible waterproof coating had been applied prior to installation.
6. Grouting: use a dry grout mix (3:1) and brush into mortar joints. Then use a light mist to set the grout. This will help when cleaning the cobbles due to corrugations in the stone.
7. Prior to grouting it is recommended that the natural stone is treated with a grout-release/sealant to prevent grout adhering onto the stone pieces.
8. It is recommended that the natural stone is sealed with a suitable sealant to protect the stone surface and to highlight the natural stone colour.
9. Where DécoR Cobbles-on-Mesh are to be laid in a non-vehicle traffic area a 100mm compacted road base can be used.
10. Sealant should be re-applied as per recommendations of the manufacture's guidelines.

IT IS RECOMMENDED THAT FOR THE BEST RESULTS, A PROFESSIONAL TRADESPERSON CARRY OUT ALL INSTALLATION WORK.

::: showroom :::
84-90 Highbury Road Burwood
Victoria
telephone: (03) 9888 9888
facsimile: (03) 9888 9884
email: sales@decorstone.com.au